



TANDBERG 150 MXP

Business-quality video communication for the individual workspace. This cost-effective solution is easy to use, provides embedded security and allows organizations to bring reliable, face-to-face communication to every employee. Use this portable system to place video and voice calls.

Integrated keypad for both voice and video calls.



DESIGN FEATURES

- Designed for personal video in any workspace
- Elegantly designed all-in-one system
- Integrated 8.4" LCD
- Ergonomically correct camera & screen position
- Integrated keypad for both voice and video calls
- Quick keys for easy control of system
- Speakerphone, headset jack for privacy or optional handset

APPLICATION FEATURES

- Business-quality visual and audio communications
- Simple user interface
- TANDBERG Expressway™ Technology
- View Presentations
- Designed for small or large scale deployment with TANDBERG Management Suite
- Optional IM and webconferencing
- URI Dialing
- H.323 & SIP support

PERFORMANCE FEATURES

- Up to 512 kbps IP
- Superior video quality incorporating the H.264 standard
- Standards-based embedded encryption (AES & DES)
- Protection against network interruptions with automatic Downsampling and IPLR
- H.235 Authentication capable and supports SIP Authentication with Microsoft Live Communication Server (LCS)

PROTECT YOUR TECHNOLOGY INVESTMENT. EXTEND THE LIFETIME OF YOUR PRODUCTS. TANDBERG's Constant Care Services fulfill customers' support needs from decision through deployment and beyond.

UNIT DELIVERED COMPLETE WITH:

8.4" LCD, integrated keypad, integrated camera & microphone, and cables

LCD SCREEN

Wide viewing angle screen
Manual brightness

BANDWIDTH

H.323 up to 512 kbps
SIP up to 512 kbps

FIREWALL TRAVERSAL

TANDBERG Expressway™ Technology
Auto NAT

VIDEO STANDARDS

H.261, H.263, H.263+, H.264

VIDEO FEATURES

Picture in Picture (PIP)
Intelligent Video Management

LIVE VIDEO RESOLUTIONS**NATIVE NTSC:**

4SIF (704 x 480 pixels) Receive only
SIF (352 x 240 pixels)

NATIVE PAL:

4CIF (704 x 576 pixels), Digital Clarity
CIF (352 x 288 pixels)
QCIF (176 x 144 pixels)
SQCIF (128 x 96 pixels) Receive only

RECEIVE NATIVE PC RESOLUTIONS:

XGA (1024 x 768 pixels)
SVGA (800 x 600 pixels)
VGA (640 x 480 pixels)

AUDIO STANDARDS

G.711, G.722, G.722.1

AUDIO FEATURES

TANDBERG acoustic echo cancellation
Automatic Gain Control (AGC)
Automatic Noise Reduction

PRIVACY FEATURE

Headset and mic via 2.5 mm mini jack with light indication (optional)
Video Privacy (mute) with light indication and far end mute indication
Audio Privacy (mute) with light indication
Camera lens cap

FRAME RATES

30 frames per second @ 168 kbps and above

EMBEDDED ENCRYPTION

Standards-based: H.235 v2&v3, DES and AES
NIST-validated AES
NIST-validated DES
Automatic key generation and exchange

IP NETWORK FEATURES

Differentiated Services (DiffServ)
Resource Reservation Protocol (RSVP)
IP precedence
IP type of service (ToS)
IP adaptive bandwidth management (including flow control)
Auto gatekeeper discovery
Dynamic playout and lip-sync buffering
Automatic support for private and public IP addresses using NAT
H.245 DTMF tones in H.323
Cisco CallManager integration using ECS
Static or Dynamic H.323 Ports
IP Downsampling
Intelligent Packet Loss Recovery (IPLR)
Intelligent Call Management
Maximum call length timer
IP Address Conflict Warning
URI Dialing

SECURITY FEATURES

IP Administration Password
Menu Administration Password
Dialing Access code
H.243 MCU Password
Disable IP services
Embedded encryption (AES & DES)
Call status light indication
Network Settings protection
SIP Authentication via NTLM

NETWORK INTERFACES

Internal 2 port Ethernet switch
1 x LAN / Ethernet (RJ-45) 10/100 Mbit for PC
1 x LAN / Ethernet (RJ-45) 10/100 Mbit for LAN / DSL / cable modem
Power-over-Ethernet (PoE - IEEE 802.3af)

ETHERNET / INTERNET / INTRANET CONNECTIVITY

TCP / IP, DHCP, ARP, FTP, Telnet, SOAP and XML, SNMP

OTHER MAJOR ITU STANDARDS SUPPORTED

H.225, H.241, H.243, H.245
RFC 3261, RFC 2237, RFC 3264, RC 3311, RFC 3550,
RFC 2032, RFC 2190, RFC 2429, RFC 3407

CAMERA

1/4" CCD
+10° / -10° tilt
32° Vertical field of view
36° Total vertical field of view
45° Horizontal field of view
48° Total horizontal field of view
460 (PAL) / 470 (NTSC) TV lines
Min. illumination 1.1 Lux (Video Output 50%, AGC ON, Standard lens)
Reference 0.4 Lux (Video Output 50%, AGC ON, F1.4)
Manual focus & brightness
Automatic white balance

CLOSED CAPTIONING

TTY (Telephone Text) support (via 2.5mm headset jack)

SYSTEM MANAGEMENT

Support for the TANDBERG Management Suite
Telnet, XML, SOAP, FTP, SNMP

DIRECTORY SERVICES

Support for Local, Global and Dynamic Server Directories
Unlimited entries using Server directory supporting LDAP and H.350*
200 number local directory
Last Number Called
Call History
Directories in Local Languages

13 SELECTABLE MENU LANGUAGES

Simplified Chinese, Traditional Chinese, English, French, German, Italian, Japanese, Korean, Norwegian, Portuguese, Russian, Spanish and Swedish

POWER

Auto-sensing power supply
100 – 250 VAC, 50 – 60 Hz
24 watts max. (12.95 with PoE 802.3af)

OPERATING TEMPERATURE AND HUMIDITY

0° C to 35° C (32° F to 95° F) ambient temperature
10% to 90% Relative Humidity (RH)

STORAGE AND TRANSPORT TEMPERATURE

-20° C to 60° C (-4° F to 140° F) at RH 10-90% (non-condensing)

APPROVALS

Directive 73/23/EEC (Low Voltage Directive)
-Standard EN 60950
Directive 89/336/EEC (EMC Directive)
-Standard EN 55022, Class B
-Standard EN 55024
-Standard EN 61000-3-2/-3-3
Approved according to UL 60950
and CAN/CSA C22.2 No. 60950
Complies with FCC15B Class B

UNIT DIMENSIONS

Height: 34.6 cm (13.6 inches)
Width: 23 cm (9 inches)
Depth: 20.4 cm (8 inches)
Footprint: 17 cm x 18.5 cm (6.68 inches x 7.3 inches)
Weight: 1.5 kg (3.3 lbs)

* Requires TANDBERG Management Suite version 9.5 or newer

System features vary depending on network selection and software package. All specifications are subject to change without notice.

All photographs and images contained in these materials are for general, representational purposes only. Actual products may differ based upon component availability.

TANDBERG is a registered trademark or trademark of TANDBERG in the U.S. and other countries.

Cisco, Cisco Systems, the Cisco Systems logo, and the Cisco Arrow logo are registered trademarks or trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries.

Service availability may vary from region to region. Please contact your TANDBERG reseller for more information.

TANDBERG

150

MPX

TANDBERG WORLD HEADQUARTERS

Philip Pedersens vei 22
1366 Lysaker, Norway
Tel: +47 67 125 125
Fax: +47 67 125 234
Video: +47 67 117 777
E-mail: tandberg@tandberg.net

200 Park Avenue, Suite 2005
New York, NY U.S.A. 10166
Tel: +1 212 692 6500
Tel: +1 800 538 2884 (toll free in the U.S.)
Fax: +1 212 692 6501
Video: +1 212 692 6535
E-mail: tandberg@tandbergusa.com

October 2005